Lubrizol Advanced Materials Pearlthane® MB-9010 Thermoplastic Polyurethane Elastomer

Category : Ceramic , Oxide , Titanium Oxide , Polymer , Thermoplastic , Polyurethane, TP

Material Notes:

Pearlthane® MB-9010 is a TPU-based color masterbatch, supplied in the form of homogenously white-colored pellets. It is specially intended for coloring TPUs (either polyester or polyether-based), for extrusion, injection molding or calendering processes. Applications: Pearlthane MB-9010 can be mixed with any items of Merquinsa's Pearlthane or Pearlcoat lines (either polyester or polyether-based) intended for applications obtained by extrusion, injection molding or calendering. A 2% usage level (on TPU, by weight) is recommended. Higher levels can be considered, depending on the requirements of the end-product. A good color consistency requires an accurate dosing and good distribution in the TPU.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubrizol-Advanced-Materials-Pearlthane-MB-9010-Thermoplastic-Polyurethane-Elastomer.php

Physical Properties	Metric	English	Comments	
Apparent Bulk Density	1.05 g/cc	0.0379 lb/in³	ASTM D-1875	
Component Elements Properties	Metric	English	Comments	

Processing Properties	Metric	English	Comments
Processing Temperature	<= 240 °C	<= 464 °F	
Drying Temperature	100 - 110 °C	212 - 230 °F	In hot air circulatory, vacuum, or desiccant-air dryer
	@Time 3600 - 7200 sec	@Time 1.00 - 2.00 hour	

Descriptive Properties	Value	Comments
Colour Index n0	RAL 9010	
Lightfastness	8	(1-8) Scale of blue tones; DIN 53 389

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China