

## **Lubrizol ESTANE® X1013 Ether Based Thermoplastic Polyurethane (European Grade)**

Category: Polymer, Thermoplastic, Elastomer, TPE, Polyurethane, TP, Thermoplastic Polyurethane, Elastomer, Ether Grade

## **Material Notes:**

Description: Estane® thermoplastic polyurethanes (TPUs) include elastomeric materials that bridge the gap between flexible rubber and rigid plastics. These materials offer toughness and durability in a flexible thermoplastic elastomer system that is easy to process in a wide range of equipment. The Estane® TPU portfolio of products offers high performance polyester - and polyether - based resins and compounds in a broad range of hardnesses to meet a variety of application needs. Benefits of Estane® TPU: Outstanding Abrasion and Wear ResistanceExcellent Low Temperature FlexibilitySuperior Toughness and DurabilityEase of Processing and Manufacturing FlexibilityColorability and Paintability with no adhesion promoterApplications: Film & SheetFabric coating & melt coatingWire & CableHose, Tube & ProfileCustom moldingCustom compoundingAutomotive interior/chassis and exterior painted trimInformation provided by Noveon, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Lubrizol-ESTANE-X1013-Ether-Based-Thermoplastic-Polyurethane-European-Grade.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.18 g/cc	1.18 g/cc	DIN 53479

Mechanical Properties	Metric	English	Comments	
Hardness, Shore D	70	70	DIN 53505	
Tensile Strength, Ultimate	42.0 MPa	6090 psi	DIN 53504	
Elongation at Break	355 %	355 %	DIN 53504	
50% Modulus	0.0204 GPa	2.96 ksi	DIN 53504	
100% Modulus	0.0213 GPa	3.09 ksi	DIN 53504	
300% Modulus	0.0358 GPa	5.19 ksi	DIN 53504	
Flexural Stiffness	430.00 MPa	62366 psi	ASTM D747	
Tear Strength	175 kN/m	999 pli	DIN 53515	
Abrasion	81	81	mm <sup>3</sup> ; DIN 53516	

Thermal Properties	Metric	English	Comments
Vicat Softening Point	99.0 °C	210 °F	A50; DIN 53460

Descriptive Properties	Value	Comments
E-Modulus	420 mm/min	



## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China