

Mallard Creek Polymers Rovene® 6016 Acrylic Emulsion

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Applications: Rovene® 6016 is recommended for various nonwoven and paper applications requiring soft hand with resistance to heat and light aging coupled with good wet strength and chemical resistance. Typical application methods include froth, saturation or coating
Storage and Handling: Protect from freezing. Ideal storage temperature is 22°C (72°F). Read the Rovene® 6016 Material Safety Data Sheet before handling, storing, or using this product
Information provided by Mallard Creek Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_Mallard-Creek-Polymers-Rovene-6016-Acrylic-Emulsion.php

Physical Properties	Metric	English	Comments
Solids Content	48 - 50 %	48 - 50 %	
Particle Size	0.19 µm	0.19 µm	
pH	3.0 - 5.0	3.0 - 5.0	
Brookfield Viscosity	<= 600 cP	<= 600 cP	#20/200

Thermal Properties	Metric	English	Comments
Glass Transition Temp, Tg	-20.0 °C	-4.00 °F	

Descriptive Properties	Value	Comments
Emulsifiers	Anionic	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China