

## MarkeTech Cu/Mo/Cu 1:4:1 Laminated Sheet

Category: Metal, Metal Matrix Composite, Nonferrous Metal, Molybdenum Alloy

## **Material Notes:**

Cu/MoCu sheets have very high in-plane thermal conductivity provide by layers of Cu and low CTEs provided by the inner layer of molybdenum. These laminated sheets spread heat from a concentrated heat source and subsequently dissipate the heat through the layers. Used as heat sinks. Data provided by the supplier, MarkeTech International.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_MarkeTech-CuMoCu-141-Laminated-Sheet.php

Physical Properties	Metric	English	Comments
Density	9.70 - 9.90 g/cc	0.350 - 0.358 lb/in³	

Thermal Properties	Metric	English	Comments
CTE, linear	6.80 - 7.20 µm/m-°C	3.78 - 4.00 µin/in-°F	
	@Temperature 20.0 - 100 °C	@Temperature 68.0 - 212 °F	
Thermal Conductivity	170 - 180 W/m-K	1180 - 1250 BTU-in/hr- ft²-°F	z direction
	210 - 220 W/m-K	1460 - 1530 BTU-in/hr- ft²-°F	x-y direction
Maximum Service Temperature, Air	850 °C	1560 °F	resists repeated cycles

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China