

Michelman® Michem® Lube 190 Anionic polyethylene wax emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Polyethylene (PE)

Material Notes:

Description: Anionic polyethylene wax emulsion Usage: Michem® Lube 190 provides mar and scratch resistance as well as improved water resistance and is useful in the coatings and graphic arts industries. Compatible with ingredients used in many industries, including: Automotive care products; Building materials; Can and coil coatings; Concrete; Cordage and twine; Deck stains and sealants; Die lubricants; Fiber sizings; Floor polishes; Furniture coatings; Glass; Gloves, balloons, footwear and mechanical seals; Inks; Packaging films; Pressure-sensitive adhesives; Textiles; Urethane foam and Varnishes When manufactured in Belgium Product meets food contact regulations for: Europe: Euro. Res. AP(2004)1 (Restricted) Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Lube-190-Anionic-polyethylene-wax-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.980 - 1.00 g/cc	0.980 - 1.00 g/cc	
Volatiles	64.5 - 65.5 %	64.5 - 65.5 %	
pH	>= 7.0	>= 7.0	Recommended pH of system
	8.7 - 9.7	8.7 - 9.7	
Brookfield Viscosity	<= 50 cP	<= 50 cP	Spindle # 2, rpm 60

Descriptive Properties	Value	Comments
Appearance	Amber, translucent liquid	
Emulsifier Charge	Anionic	
Solids Type	High Density Polyethylene	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China