

Momentive Performance Materials Contractors SCS 1000[®] Construction Sealant

Category : Polymer , Adhesive , Thermoset , Silicone , Silicone, RTV, Construction Grade

Material Notes:

One-part, for general purpose glazing and sealing applications. Cure Method: Acetoxy. Tack-free time

Order this product through the following link:

http://www.lookpolymers.com/polymer_Momentive-Performance-Materials-Contractors-SCS-1000-Construction-Sealant.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	29	29	ASTM D2240
Tensile Strength, Ultimate	2.20 MPa	319 psi	ASTM D412

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	204 Â°C	399 Â°F	Elasticity is retained to this temperature.
Minimum Service Temperature, Air	-62.0 Â°C	-79.6 Â°F	Elasticity is retained to this temperature.

Processing Properties	Metric	English	Comments
Processing Temperature	25.0 Â°C	77.0 Â°F	Cure time to 0.25 in. is 5-7 days

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China