

Momentive Performance Materials TSE326 Red Adhesive Sealant, Non-Corrosive Flowable High Temperature

Category : Polymer , Adhesive , Thermoset , Silicone , Silicone, RTV, Adhesive/Sealant Grade

Material Notes:

One-part heat cure. Typical uses: Assembly and gasketing. Data provided by the manufacturer, GE Silicones. GE Silicones became a part of Momentive Performance Materials in 2006.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Momentive-Performance-Materials-TSE326-Red-Adhesive-Sealant-Non-Corrosive-Flowable-High-Temperature.php

Physical Properties	Metric	English	Comments
Density	1.45 g/cc	0.0524 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	43	43	
Tensile Strength, Ultimate	3.43 MPa	497 psi	
Elongation at Break	170 %	170 %	

Electrical Properties	Metric	English	Comments
Dielectric Constant	3.3	3.3	
Dielectric Strength	22.0 kV/mm	559 kV/in	

Processing Properties	Metric	English	Comments
Processing Temperature	100 °C	212 °F	Cure time 2 hr at this temperature.

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China