

NIZHNEKAMSKNEFTEKHIM PP 8300K (EPT30R) Propylene and Ethylene Block Polymer

Category: Polymer, Thermoplastic, Polyethylene (PE), Polypropylene (PP)

Material Notes:

Product obtained by copolymerization of propylene with ethylene in presence of complex metalorganic catalysts. It incorporates increased long-term thermal stability, thermal-oxidative degradation resistance when PP is produced, processed and PP-made articles are exploited. Information provided by manufacturer

Order this product through the following link:

http://www.lookpolymers.com/polymer_NIZHNEKAMSKNEFTEKHIM-PP-8300K-EPT30R-Propylene-and-Ethylene-Block-Polymer.php

Physical Properties	Metric	English	Comments
Melt Flow	3.0 - 4.0 g/10 min	3.0 - 4.0 g/10 min	ASTM D1238/L
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	

Mechanical Properties	Metric	English	Comments
Flexural Modulus	>= 1.10 GPa	>= 160 ksi	ASTM D790
Izod Impact, Notched	>= 0.500 J/cm	>= 0.937 ft-lb/in	ASTM D256
1200 IIIIpact, Notched	@Temperature -20.0 °C	@Temperature -4.00 °F	
	>= 1.60 J/cm	>= 3.00 ft-lb/in	ASTM D256
	@Temperature 23.0 °C	@Temperature 73.4 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China