

NanoAmor 94%, OD/WT/L: 20-50/1-2 nm/0.5-2 um Multi-Walled Carbon Nanotubes

Category : Carbon

Material Notes:

Applications Additives in polymers Catalysts Electron field emitters for cathode ray lighting elements, flat panel display, gas-discharge tubes in telecom networks Electromagnetic-wave absorption and shielding Energy conversion Lithium-battery anodes Hydrogen storage Nanotube composites (by filling or coating); Nanoprobes for STM, AFM, and EFM tips, nanolithography, nanoelectrodes, drug delivery, sensors Reinforcements in composites Supercapacitor Information provided by NanoAmor Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_NanoAmor-94-ODWTL-20-501-2-nm05-2-um-Multi-Walled-Carbon-Nanotubes.php

Physical Properties	Metric	English	Comments
Apparent Bulk Density	0.290 g/cc	0.0105 lb/in ³	
Particle Size	0.0010 - 0.0020 µm	0.0010 - 0.0020 µm	wall thickness
	0.020 - 0.050 µm	0.020 - 0.050 µm	outside diameter

Descriptive Properties	Value	Comments
Color	black	
Length (um)	0.5-2	
Purity (vol% carbon nanotubes), min	94	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China