

Neutrex Purgex™ 3057 Plus Purging Compound

Category : Polymer , Thermoplastic , Purging Compound

Material Notes:

Blend, polyethylene, 3% glass, and FDA-approved active component. Non-toxic, non-abrasive and safe. Ready to use and easy to removePURGEX 3057 Plus thoroughly removes all types of colorants and engineering resins, such as nylon and polycarbonate, from the barrel, screw, and nozzle of thermoplastic resin injection molding, extrusion, or blow molding equipment, as well as hot runner systems. PURGEX 3057 Plus includes a modified polyethylene for higher temperature resins. PURGEX 3057 Plus can be used for rapid turnaround on color and material hanges with challenging resins such as LCP, PBT, and PPO, on alloys such as PC/ABS, and is recommended for glass- or mineral-filled applications. This blend operates up to 600°F (316°C) with a five minute soak, or higher temperatures without a soak.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Neutrex-Purgex-3057-Plus-Purging-Compound.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 - 316 °C	300 - 600 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China