

Neutrex Purgex™ 456 Plus Purging Compound

Category : Polymer , Thermoplastic , Purging Compound

Material Notes:

Blend, polyethylene, and FDA-approved active component. Non-toxic, non-abrasive, and safe. Ready to use and easy to remove. PURGEX 456 Plus is used for color and/or material changes and the removal of residual contamination in thermoplastic injection molding, extrusion, or blow molding equipment. PURGEX 456 Plus will efficiently purge the barrel, screw, and nozzle, as well as hot runners. This blend removes all types of colorants and commodity resins, including polypropylene, polyethylene, and their copolymers. PURGEX 456 Plus is used to neutralize HCl gasses in PVC purging applications. PURGEX 456 Plus assures rapid turnaround on color and material changes with polyolefins and their copolymers, styrenics polymers, acetals, vinyls, TPO, TPU, and many more resins processed in this temperature range.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Neutrex-Purgex-456-Plus-Purging-Compound.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	138 - 288 °C	280 - 550 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China