

Niche Polymer PPCG20BK Copolymer PP, 20% Glass Fiber Filled

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene Copolymer , Polypropylene with 20% Glass Fiber Filler

Material Notes:

Information provided by Niche Polymer

Order this product through the following link:

http://www.lookpolymers.com/polymer_Niche-Polymer-PPCG20BK-Copolymer-PP-20-Glass-Fiber-Filled.php

Physical Properties	Metric	English	Comments
Linear Mold Shrinkage	0.00400 - 0.00700 cm/cm	0.00400 - 0.00700 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	60.7 MPa	8800 psi	ASTM D638
Elongation at Break	7.00 - 12.0 %	7.00 - 12.0 %	ASTM D638
Flexural Strength	73.1 MPa	10600 psi	ASTM D790
Flexural Modulus	3.31 GPa	480 ksi	ASTM D790
Izod Impact, Unnotched	0.908 J/cm @Thickness 3.17 mm	1.70 ft-lb/in @Thickness 0.125 in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	138 °C	280 °F	ASTM D648

Processing Properties	Metric	English	Comments
Melt Temperature	149 - 171 °C	300 - 340 °F	ASTM D789

Descriptive Properties	Value	Comments
Color	Black	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China