

Nitriflex Nitrilatex NTL-610 Acrylonitrile Butadiene Latex

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

NITRILATEX synthetic lattices are divided into several groups, modified or not with carboxylic acid. Applications: NITRILATEX synthetic lattices are specially indicated to impregnate cords, adhesives manufacture, fibers agglomeration, supported gloves manufacture, impregnation of non-woven, etc. Information provided by Dax Resinas

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nitriflex-Nitrilatex-NTL-610-Acrylonitrile-Butadiene-Latex.php

Physical Properties	Metric	English	Comments
Solids Content	38 - 40 %	38 - 40 %	Method L-001/P-065; ASTM D1417
pH	9.5 - 12	9.5 - 12	25°C, Method L-003; ASTM D1417
Brookfield Viscosity	60 cP	60 cP	(spindle=1, 20 rpm); ASTM D1417
Surface Tension	<= 50 dynes/cm	<= 50 dynes/cm	Method L-005/L-040; ASTM D1417

Descriptive Properties	Value	Comments
Bound Acrylonitrile Content (%)	37 - 41	ASTM D3533

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China