

Nitriflex SB-4022 Styrene Butadiene Copolymer

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE) , Styrene Butadiene Rubber

Material Notes:

Applications: Powdered rubber. Enables a lower mixing time and better homogenization, presenting a reduced generation of residues.

Recommended for shoe soles, adhesives and seals, injected and molded artifacts. Information provided by Dax Resinas

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nitriflex-SB-4022-Styrene-Butadiene-Copolymer.php

Physical Properties	Metric	English	Comments
Volatiles	0.00 - 0.75 %	0.00 - 0.75 %	Method B-003; ASTM D5668
Particle Size	<= 1000 µm	<= 1000 µm	99-100%; ASTM D1921
Mooney Viscosity	46 - 58 @Temperature 100 °C	46 - 58 @Temperature 212 °F	MML 1+4, Method B-002; ASTM D1646

Chemical Properties	Metric	English	Comments
Styrene Content	22.5 - 24.5 %	22.5 - 24.5 %	ASTM D5775

Descriptive Properties	Value	Comments
CaCO3 Partitioning Agent Content %	10 to 14	Method B-035

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China