

Orion Engineered Carbons CORAX® N 660 ASTM Carbon Black

Category : Carbon , Carbon Black

Material Notes:

Standard grade of furnace black in accordance with the requirements of ASTM D 1765 Soft Black - carcass grade, semi-reinforcing carbon black. Information provided by Orion Engineered Carbons.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Orion-Engineered-Carbons-CORAX-N-660-ASTM-Carbon-Black.php

| Physical Properties | Metric | English | Comments |
|--------------------------|----------------------|---------------------------|---|
| Bulk Density | 0.440 g/cc | 0.0159 lb/in ³ | Pour Density; ASTM D 1513 |
| Oil Absorption | 74 % | 74 % | (ml/100 g); Compressed Sample; ASTM D 3493 |
| | 90 % | 90 % | (ml/100 g); ASTM D 2414 |
| Loss On Ignition | <= 1.0 % | <= 1.0 % | Heating Loss; ASTM D 1509 |
| Specific Surface Area | 34 m ² /g | 34 m ² /g | Statistical thickness surface area; ASTM D 6556 |
| Iodine Absorption Number | 36 | 36 | mg/g; ASTM D 1510 |

| Descriptive Properties | Value | Comments |
|----------------------------|-----------|-----------------------------------|
| Fines | < 7.0 % | ASTM D 1508 |
| Individual Pellet Hardness | < 45 g | ASTM D 5230, average 1.4 - 1.7 mm |
| Sieve Residue | < 300 ppm | ASTM D 1514 |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China