

Parker Chomerics PORCUPINE METALASTIC® Gasketing Wire Mesh EMI Gasket Selection Guide

Category : Metal

Material Notes:

Construction: Expanded Metal in Elastomer Available Forms: Sheets, Die-Cut Gaskets Standard Metals Available in EMI Portion: Monel Aluminum Information provided by Chomerics

Order this product through the following link:

http://www.lookpolymers.com/polymer_Parker-Chomerics-PORCUPINE-METALASTIC-Gasketing-Wire-Mesh-EMI-Gasket-Selection-Guide.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	204 °C	399 °F	Silicone Version
Minimum Service Temperature, Air	-62.0 °C	-79.6 °F	Silicone Version

Electrical Properties	Metric	English	Comments
Shielding Effectiveness	>= 35 dB	>= 35 dB	
	@Frequency 14000 Hz	@Frequency 14000 Hz	
	>= 85 dB	>= 85 dB	
	@Frequency 1.00e+9 Hz	@Frequency 1.00e+9 Hz	
	>= 102 dB	>= 102 dB	
	@Frequency 1.80e+7 Hz	@Frequency 1.80e+7 Hz	

Descriptive Properties	Value	Comments
Maximum Joint Unevenness, % of Gasket Height	0.1	Class B- Open-Close in Same Position
	0.1	Class C- Completely Interchangeable
	0.15	Class A- Permanently Closed

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China