

Parker Chomerics Tecknit Teckshield®-F 100 OPI 0.002" Diameter Wire, Allycarbonate EMI Shielding Window

Category : Polymer

Material Notes:

Description: Tecknit Allylcarbonate shielded windows are manufactured by casting a woven EMI shield mesh into a material that has optical properties similar to that of glass. The window offers a lightweight, cost effective alternative to traditional glass laminated shielded windows and is a more flexible material to machine, making it more suited to meet the changing design demands that are part of modern electronics. Application Information: Allylcarbonace windows are ideally suited to applications where there is a requirement to shield displays or visual apertures. Windows are machined using computerized programming technologyInformation provided by Chomerics

Order this product through the following link:

http://www.lookpolymers.com/polymer_Parker-Chomerics-Tecknit-Teckshield-F-100-OPI-0002-Diameter-Wire-Allycarbonate-EMI-Shielding-Window.php

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	97	97	ASTM D785

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	100 °C	212 °F	
	130 °C	266 °F	1 hour duration
Minimum Service Temperature, Air	-60.0 °C	-76.0 °F	
	-60.0 °C	-76.0 °F	1 hour duration

Optical Properties	Metric	English	Comments
Transmission, Visible	93.3 %	93.3 %	ASTM D1003

Electrical Properties	Metric	English	Comments
Shielding Effectiveness	40 dB	40 dB	Plane Wave
	@Frequency 1.00e+10 Hz	@Frequency 1.00e+10 Hz	
	55 dB	55 dB	H-Field
	@Frequency 100000 Hz	@Frequency 100000 Hz	
	60 dB	60 dB	Plane Wave
	@Frequency 1.00e+9 Hz	@Frequency 1.00e+9 Hz	
	120 dB	120 dB	
	@Frequency 1.00e+7	@Frequency 1.00e+7	E-Field



Electrical Properties

Hz Metric Hz English Comments

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China