

PlastxWorld CEVIAN® B6524 20% GF PBT/ABS Alloy

Category : Polymer , Thermoplastic , ABS Polymer , ABS/Polyester Alloy + GF , Polyester, TP , Polybutylene Terephthalate (PBT)

Material Notes:

Glass fiber and mineral filled, low warpage and flame retarded PBT/ABS. Information provided by PlastxWorld Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_PlastxWorld-CEVIAN-B6524-20-GF-PBTABS-Alloy.php

Physical Properties	Metric	English	Comments
Density	1.43 g/cc	0.0517 lb/in ³	ASTM D792
Linear Mold Shrinkage	0.0025 - 0.0045 cm/cm	0.0025 - 0.0045 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	58.6 MPa	8500 psi	ASTM D638
Elongation at Break	2.0 %	2.0 %	ASTM D638
Flexural Yield Strength	97.9 MPa	14200 psi	ASTM D790
Flexural Modulus	5.10 GPa	740 ksi	ASTM D790
Izod Impact, Notched	0.374 J/cm @Thickness 3.17 mm	0.700 ft-lb/in @Thickness 0.125 in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	116 °C	241 °F	0.25 inch; ASTM D648
Flammability, UL94	V-0 @Thickness 1.70 mm	V-0 @Thickness 0.0669 in	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China