

PolyMirae Moplen HP526N IPP/WQBF Grade Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Film Grade

Material Notes:

Moplen HP526N is the polypropylene homopolymer manufactured by PMC under the license of BASELL using the Spheripol process. Moplen HP526N is a homopolymer particularly suitable for WQB (Water Quenching Blown) film. Moplen HP526N resin meets the FDA requirements in the Code of Federal Regulations in 21 CFR 178.2010 for food packaging substances with adequate additives. And contains no dangerous substances according to Federal Regulations in 21 CFR 177.1520. Features: High Transparency and gloss; High slip and antiblocking; High stiffness; Good sealability Applications: Packaging; Foodstuffs; Stationary items Information provided by PolyMirae Company Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_PolyMirae-Moplen-HP526N-IPPWQBF-Grade-Polypropylene.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in ³	ASTM D1505
Melt Flow	12 g/10 min @Load 2.16 kg, Temperature 230 °C	12 g/10 min @Load 4.76 lb, Temperature 446 °F	Condition L; ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	101	101	ASTM D785
Tensile Strength, Yield	34.3 MPa	4980 psi	ASTM D638
Elongation at Yield	12 %	12 %	ASTM D638
Flexural Modulus	1.52 GPa	220 ksi	ASTM D790
Izod Impact, Notched	0.392 J/cm	0.735 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	105 °C	221 °F	ASTM D648
Vicat Softening Point	155 °C	311 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China