

PolyOne Maxxam™ MAXBATCH YM-618.G001-1000 Polypropylene, Unspecified (PP, Unspecified)

Category: Polymer, Thermoplastic, Polypropylene (PP)

Material Notes:

PolyOne's Maxxam™ family of polypropylene- and polyethylene-based products covers a wide range of applications, markets and performance requirements. Standard grades are compounded with calcium carbonate, glass and talc to provide a desired balance of properties including stiffness, durability, impact resistance and heat resistance. Custom grades are available with features such as UV stabilizers, heat stabilizers, custom color, high impact, etc.MAXBATCH PRODUCTS ARE DESIGNED TO BE USED AS A LETDOWN WITH ADDITIONAL POLYPROPYLENE.Information provided by PolyOne

Order this product through the following link:

http://www.lookpolymers.com/polymer_PolyOne-Maxxam-MAXBATCH-YM-618G001-1000-Polypropylene-Unspecified-PP-Unspecified.php

Physical Properties	Metric	English	Comments	
Specific Gravity	1.70 g/cc	1.70 g/cc	ASTM D792	
Melt Flow	1.8 g/10 min	1.8 g/10 min		
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	Procedure A; ASTM D1238	

Descriptive Properties	Value	Comments
Appearance	Natural Color	
Features	General Purpose	
Filler / Reinforcement	Talc Filler	
	Unspecified FillerReinfor., 70% Filler by Weight	
Forms	Pellets	
Generic Material	PP, Unspecified	
Generic Name	Polypropylene, Unspecified (PP, Unspecified)	
Processing Method	Injection Molding	
Regional Availability	Africa & Middle East	
	Asia Pacific	
	Europe	
	North America	
	South America	
Uses	Automotive Applications	

Automotive Applications



Descriptive Properties	Value Construction Applications	Comments
	Consumer Applications	
	General Purpose	
	Industrial Applications	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China