

PolyOne Maxxam™ MULTI PURGE 1600 Polyolefin, Unspecified

Category : Polymer , Thermoplastic , Polyolefin

Material Notes:

PolyOne's Maxxam™ family of polypropylene- and polyethylene-based products covers a wide range of applications, markets and performance requirements. Standard grades are compounded with calcium carbonate, glass and talc to provide a desired balance of properties including stiffness, durability, impact resistance and heat resistance. Custom grades are available with features such as UV stabilizers, heat stabilizers, custom color, high impact, etc. Information provided by PolyOne

Order this product through the following link:

http://www.lookpolymers.com/polymer_PolyOne-Maxxam-MULTI-PURGE-1600-Polyolefin-Unspecified.php

Physical Properties	Metric	English	Comments
Melt Flow	1.0 g/10 min @Load 2.16 kg, Temperature 230 °C	1.0 g/10 min @Load 4.76 lb, Temperature 446 °F	Procedure A; ASTM D1238

Descriptive Properties	Value	Comments
Appearance	Natural Color	
Features	General Purpose	
Forms	Pellets	
Generic Material	Polyolefin, Unspecified	
Generic Name	Polyolefin, Unspecified	
Processing Method	Injection Molding	
Regional Availability	North America	
Uses	Purging Compound	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China