

## PolyOne OnColor™ F Polyester, Thermoplastic (Polyester, TP)

Category : Polymer , Thermoplastic , Polyester, TP

### Material Notes:

Information provided by PolyOne

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_PolyOne-OnColor-F-Polyester-Thermoplastic-Polyester-TP.php](http://www.lookpolymers.com/polymer_PolyOne-OnColor-F-Polyester-Thermoplastic-Polyester-TP.php)

Processing Properties	Metric	English	Comments
Melt Temperature	266 - 299 °C	511 - 570 °F	Blow Molding

Descriptive Properties	Value	Comments
Agency Ratings	FDA Unspecified Rating	
Appearance	Clear/Transparent	
	Opaque	
	Translucent	
Carrier Resin	Wax or Wax Blend	
Colorant	Proprietary	
Forms	Flakes	
	Pellets	
Generic Material	Polyester, TP	
Generic Name	Polyester, Thermoplastic (Polyester, TP)	
Loading	0.010 to 85%	
Polymer Compatibility	PET, PETG	
Processing Method	Blow Molding	
	Extrusion	
	Injection Molding	
Regional Availability	Africa & Middle East	
	Asia Pacific	
	Europe	
	North America	

Descriptive Properties	South America Value	Comments
Usage Rate	0.010 to 10%	
Uses	Bottles	
	Packaging	
	Sheet	

**Contact Songhan Plastic Technology Co.,Ltd.**

Website : [www.lookpolymers.com](http://www.lookpolymers.com)  
Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)  
Tel : +86 021-51131842  
Mobile : +86 13061808058  
Skype : lookpolymers  
Address : United North Road 215,Fengxian District, Shanghai City,China