

## Precision Polymer Engineering V70H Fluoroelastomer Compound

Category : Polymer , Thermoset , Fluoropolymer, TS , Thermoset Fluoroelastomer , Rubber or Thermoset Elastomer (TSE)

## Material Notes:

Fluoroelastomer Rubber, 66-75 °IRHD. Copolymer of vinylidene fluoride and hexafluoropropylene. Formulated using only those ingredients determined by the United States Federal Food and Drug Administration (FDA). Water and n-Hexane extraction tested in accordance with Code of Federal Regulations Title 21 (CFR21), Section 177.2600. ASTM designation = FKM. ISO designation = FPM. . Also complies to the requirements of USP 25, NF20, 2002, Class 6.Applications: Excellent oil and heat resistance. For repeated use in equipment associated with the production of foodstuffs intended for human consumption. For use with aqueous or fatty foods.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Precision-Polymer-Engineering-V70H-Fluoroelastomer-Compound.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	74	74	°IRHD; ASTM D1415
	59 - 89	59 - 89	°IRHD, ±15 change after 72 hours @ 250°C; ASTM D1415
Tensile Strength, Yield	12.0 MPa	1740 psi	ASTM D412
	8.40 - 15.6 MPa	1220 - 2260 psi	±30% change after 72 hours @ 250°C; ASTM D412
Elongation at Break	100 %	100 %	-50% change after 72 hours @ 250°C; ASTM D412
	200 %	200 %	ASTM D412
Compression Set	20 %	20 %	24 hours @ 200°C; ASTM D395

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	200 °C	392 °F	
Minimum Service Temperature, Air	-10.0 °C	14.0 °F	
Flash Point	>= 315 °C	>= 599 °F	

Descriptive Properties	Value	Comments
Extraction Test, 21 CFR 177.2600	pass	Distilled Water
	pass	n-Hexane

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com



Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China