

## Premix Thermoplastics PREWHITE PP 22-50

Category : Polymer , Thermoplastic , Polypropylene (PP)

**Material Notes:**

PREWHITE PP 22-50 is a polypropylene based white masterbatch developed for polypropylene extrusion coating applications. Due to the overall balance in the formulation, fast line speeds up to 300 m/min and low coating weights down to 10 g/m<sup>2</sup> can be achieved. According to FDA and BgVV regulations PREWHITE PP 22-50 is approved for use in contact with foodstuffs without limitations. Information provided by Premix Thermoplastics Inc.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Premix-Thermoplastics-PREWHITE-PP-22-50.php](http://www.lookpolymers.com/polymer_Premix-Thermoplastics-PREWHITE-PP-22-50.php)

Physical Properties	Metric	English	Comments
Density	1.50 g/cc	0.0542 lb/in <sup>3</sup>	
Additive Loading	50 %	50 %	TiO <sub>2</sub> (rutile)

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	300 °C	572 °F	30% Masterbatch

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.15 %	<= 0.15 %	When Produced
Shelf Life	12.0 Month	12.0 Month	Normal Storing Conditions

Descriptive Properties	Value	Comments
Appearance	Granule	
Carrier	Extrusion Coating PP	
Dosing, %	30 max	Predrying at 3 hours at 90°C is recommended
Light Fastness	8-Very Good	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China