

Protective Coating PC-Wood Guardian™ Wood Preservative

Category : Other Engineering Material

Material Notes:

PC-Wood Guardian™ is used in preventing and controlling decay fungi. It is an effective treatment for wood and wood composite to kill and prevent infestations of decay fungi including white and brown rot and wet rot. It is also effective for the prevention and control of wood destroying insects including, but not limited to, Subterranean Termites, Drywood Termites, Dampwood Termites, Powderpost Beetles, Deathwatch and Furniture Beetles, Carpenter Ants and Bark and Timber Beetles. Application is usually made by mixing with water. It may also be used as a powder and dusted onto wood or wood composites. Data provided by the manufacturer.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Protective-Coating-PC-Wood-Guardian-Wood-Preservative.php

Physical Properties	Metric	English	Comments
Bulk Density	0.320 - 0.480 g/cc	0.0116 - 0.0173 lb/in ³	
Solubility in Water	9.7 %	9.7 %	
	@Temperature 20.0 °C	@Temperature 68.0 °F	
pH	34.3 %	34.3 %	
	@Temperature 50.0 °C	@Temperature 122 °F	
pH	7.6	7.6	10% solution
	8.3	8.3	3% solution

Thermal Properties	Metric	English	Comments
Melting Point	815 °C	1500 °F	

Descriptive Properties	Value	Comments
CAS Number of Main Component	12280-03-4	
Color	White	
Consistency	Fine Powder	
Main component	Disodium Octaborate Tetrahydrate (98%)	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China