

SABIC Innovative Plastics LNP LUBRICOMP RCL36XXP PA 66 (Europe-Africa-Middle East)

Category : Polymer , Thermoplastic , Nylon , Nylon 66

Material Notes:

LNP* LUBRICOMP* RCL36XXP is a compound based on PA 66 resin, containing Carbon Fiber, PTFE. Added features include: Electrically Conductive, Internally Lubricated.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SABIC-Innovative-Plastics-LNP-LUBRICOMP-RCL36XXP-PA-66-Europe-Africa-Middle-East.php

Physical Properties	Metric	English	Comments
Density	1.37 g/cc	0.0495 lb/in ³	ISO 1183

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	220 MPa	31900 psi	5 mm/min; ISO 527
Elongation at Break	1.6 %	1.6 %	5 mm/min; ISO 527
Flexural Yield Strength	315 MPa	45700 psi	2 mm/min; ISO 178
Flexural Modulus	17.6 GPa	2550 ksi	2 mm/min; ISO 178
Izod Impact, Notched (ISO)	9.00 kJ/m ²	4.28 ft-lb/in ²	80*10*4; ISO 180/1A
Izod Impact, Unnotched (ISO)	60.0 kJ/m ²	28.6 ft-lb/in ²	80*10*4; ISO 180/1U

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	251 Â°C	484 Â°F	Flatw 80*10*4 sp=64mm; ISO 75/Af

Electrical Properties	Metric	English	Comments
Surface Resistance	10 - 1000 ohm	10 - 1000 ohm	ASTM D257

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China