

SGL Carbon Group PANOX® FA C063 SSC High performance Crimped staple oxidized textile fiber, For felts and non-wovens

Category : Carbon , Carbon Fiber , Other Engineering Material , Composite Fibers

Material Notes:

PANOX® is the industry standard when it comes to fire-retardant textile fibers. As an oxidized, thermally stabilized polyacrylonitrile (PAN) fiber that will not burn, melt, soften or drip, PANOX is ideal for processing into yarns, woven fabrics, nonwovens and felts. Information provided by SGL Carbon Group

Order this product through the following link:

http://www.lookpolymers.com/polymer_SGL-Carbon-Group-PANOX-FA-C063-SSC-High-performance-Crimped-staple-oxidized-textile-fiber-For-felts-and-non-wovens.php

Physical Properties	Metric	English	Comments
Density	1.39 - 1.43 g/cc	0.0502 - 0.0517 lb/in ³	Fiber Density
Filament Diameter	13 Åµm	13 Åµm	
Fiber Count	1.67 dtex	1.50 denier	

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	190 MPa	27600 psi	
Elongation at Break	15 - 27 %	15 - 27 %	
Tenacity	>= 0.140 N/tex	>= 1.59 g/denier	

Descriptive Properties	Value	Comments
Mean Fiber Length, mm	63	
Typical Finish Content, %	1	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China