

SK Chemicals SKYTHANE® 360D S series Polyurethane

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane, TP

Material Notes:

SKYTHANE is a thermoplastic polyurethane elastomer (TPU). Like materials ranging from rubber to plastics, it has excellent physical properties such as anti-abrasion, oil-resistance and mechanical property. It is widely used for automotive parts and various industrial parts. Information provided by SK Chemicals

Order this product through the following link:

http://www.lookpolymers.com/polymer_SK-Chemicals-SKYTHANE-360D-S-series-Polyurethane.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.25 g/cc	1.25 g/cc	ASTM D792
Linear Mold Shrinkage	0.0040 cm/cm	0.0040 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	63	63	ASTM D2240
Tensile Strength, Ultimate	41.2 MPa	5970 psi	ASTM D412
Tensile Strength, Yield	24.5 MPa @Strain 100 %	3560 psi @Strain 100 %	ASTM D412
	38.2 MPa @Strain 300 %	5550 psi @Strain 300 %	ASTM D412
Elongation at Break	420 %	420 %	ASTM D412
Resilience	40	40	by vertical rebound; ASTM D2632
Tear Strength	216 kN/m	1230 pli	Die C; ASTM D624
Taber Abrasion, mg/1000 Cycles	80	80	H18 Wheel; 1000g load; ASTM D1044

Thermal Properties	Metric	English	Comments
Vicat Softening Point	120 Å°C	248 Å°F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China