

## SK Chemicals SKYTHANE® 392A S series Polyurethane

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane, TP

### Material Notes:

SKYTHANE is a thermoplastic polyurethane elastomer (TPU). Like materials ranging from rubber to plastics, it has excellent physical properties such as anti-abrasion, oil-resistance and mechanical property. It is widely used for automotive parts and various industrial parts. Information provided by SK Chemicals

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_SK-Chemicals-SKYTHANE-392A-S-series-Polyurethane.php](http://www.lookpolymers.com/polymer_SK-Chemicals-SKYTHANE-392A-S-series-Polyurethane.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.21 g/cc	1.21 g/cc	ASTM D792
Linear Mold Shrinkage	0.0040 cm/cm	0.0040 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	93	93	ASTM D2240
Hardness, Shore D	50	50	ASTM D2240
Tensile Strength, Ultimate	44.1 MPa	6400 psi	ASTM D412
Tensile Strength, Yield	9.81 MPa @Strain 100 %	1420 psi @Strain 100 %	ASTM D412
	19.6 MPa @Strain 300 %	2840 psi @Strain 300 %	ASTM D412
Elongation at Break	650 %	650 %	ASTM D412
Resilience	37	37	by vertical rebound; ASTM D2632
Tear Strength	118 kN/m	672 pli	Die C; ASTM D624
Taber Abrasion, mg/1000 Cycles	35	35	H18 Wheel; 1000g load; ASTM D1044

Thermal Properties	Metric	English	Comments
Vicat Softening Point	110 °C	230 °F	ASTM D1525

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China