

SK Chemicals SKYTHANE® UB310 Co-Extruding Adhesive

Category : Polymer , Adhesive , Thermoplastic , Elastomer , TPE , Polyurethane , TP

Material Notes:

Description: SK Chemicals has supplied Thermoplastic Polyurethane Elastomer (TPU) under the name of SKYTHANE. UB series are used for adhesives and coating applications such as binder for magnetic tapes and inks, adhesives for shoe industries and PVC lamination, etc. UB series have good solubility to various kinds of industrial solvents and cover a wide range of solution viscosity. These special hotmelt grades can be co-extruded as an adhesive for fire hoses and converted into thin film or powder. Films are used for lamination of textiles, non-woven, plastic sheets, etc. They show good flexibility over a wide range of application temperatures. Powders are used for interlining of fiber substrates. No solvent emission occurs with these grades because they are used through hotmelt process. Information provided by SK Chemicals.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SK-Chemicals-SKYTHANE-UB310-Co-Extruding-Adhesive.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	95	95	ASTM D2240
Tensile Strength, Ultimate	41.2 MPa	5970 psi	ASTM D412
Elongation at Break	900 %	900 %	ASTM D412
100% Modulus	0.00461 GPa	0.668 ksi	ASTM D412
300% Modulus	0.00539 GPa	0.782 ksi	ASTM D412
Tear Strength	83.4 kN/m	476 pli	ASTM D624

Thermal Properties	Metric	English	Comments
Melting Point	69.0 Â°C	156 Â°F	ASTM D3418
Ring & Ball Softening Point	120 Â°C	248 Â°F	ASTM E28

Descriptive Properties	Value	Comments
Appearance	Opaque Granule	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China