

SMAC CABLEÂ® 2521S-40-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLEÂ® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Screws: Inox A2Threaded insert: Stainless steelStandard treatment: SurTec 650Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2521S-40-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	1255 daN	45.0 mm, up
	250.0 daN	102.0 mm, 45Â° down and out
	375.0 daN	70.0 mm, left and right
	400.0 daN	68.0 mm, down
	417.0 daN	67.3 mm, up and down
F, Max Static	100.0 daN	22.5 mm, 45Â° down and out
	135.0 daN	12.5 mm, down
	135.0 daN	10.0 mm, up
	67.0 daN	22.1 mm, up and down
	67.0 daN	24.0 mm, left and right
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China