

SMAC CABLE® 2525S-30-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLE® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Screws: Inox A2 Threaded insert: Stainless steel Standard treatment: SurTec 650 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2525S-30-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 °C	356 - 572 °F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	1100 daN	50.0 mm, up and down
	1390 daN	55.0 mm, 45° down and out
	1500 daN	60.0 mm, left and right
	2600 daN	64.5 mm, down
	3600 daN	40.0 mm, up
F, Max Static	1000 daN	13.8 mm, down
	1000 daN	10.0 mm, up
	400.0 daN	13.8 mm, up and down
	400.0 daN	14.0 mm, left and right
	500.0 daN	12.5 mm, 45° down and out
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China