

SPS Guang Zhou POLLITE,ç 1002G30 Flame-retarded/GF30%-Polycarbonate

Category : Polymer , Thermoplastic , Polycarbonate (PC) , Polycarbonate, Glass Fiber Filled, Flame Retardant

Material Notes:

Characteristic: High mechanical properties, high rigidity, high heat resistant, good dimensional stability, good flame retardance
Applications: E/E parts, power tool, office supplies
Information Provided by SPS (Guang Zhou) Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SPS-Guang-Zhou-POLLITE-1002G30-Flame-retardedGF30-Polycarbonate.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.43 g/cc	1.43 g/cc	ASTM D792
Melt Flow	3.0 g/10 min	3.0 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	120 MPa	17400 psi	ASTM D638
Flexural Strength	155 MPa	22500 psi	
Flexural Modulus	6.70 GPa	972 ksi	
Izod Impact, Notched	0.850 J/cm	1.59 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	152 Â°C	306 Â°F	ASTM D648
Flammability, UL94	V-0	V-0	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China