

## SSAB Tunnplat Domex® 690XP Extra High-strength Cold-forming Steel

Category: Metal, Ferrous Metal, Alloy Steel, Low Alloy Steel

## **Material Notes:**

Extra High-strength Cold-forming Steel, HSLACharacteristics: Domex® is the brand name of hot rolled products from SSAB Tunnplat. Domex® cold-forming steels are modern structural steels. General use of Domex® high strength steels offers a number of benefits compared to ordinary structural steels: Lower weight, Simpler production, Lower creep rate, Longer useful life, Higher load-bearing capacity, Lower transport costs, Reduced stocks, Lower overall cost.Iron content is approximate - exact value is not reported by the manufacturer.Data provided by SSAB Tunnplat.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_SSAB-Tunnplat-Domex-690XP-Extra-High-strength-Cold-forming-Steel.php

| Physical Properties | Metric    | English      | Comments            |
|---------------------|-----------|--------------|---------------------|
| Density             | 7.87 g/cc | 0.284 lb/in³ | Estimated by MatWeb |

| Mechanical Properties      | Metric     | English       | Comments  |
|----------------------------|------------|---------------|---|
| Tensile Strength, Ultimate | >= 750 MPa | >= 109000 psi |   |
| Tensile Strength, Yield    | >= 690 MPa | >= 100000 psi |   |
| Elongation at Break        | >= 15 %    | >= 15 %       | A <sub>5</sub>  |
| Bend Radius, Minimum       | >= 1.0 t   | >= 1.0 t      | t<3mm; internal bend radius, 90°                          |
|                            | >= 1.5 t   | >= 1.5 t      | 3 mm < t< 6mm; internal bend radius, $90 \hat{A}^{\circ}$ |
|                            | >= 2.0 t   | >= 2.0 t      | t>6mm; internal bend radius, 90°                          |

| Component Elements Properties | Metric | English | Comments |  |
|-------------------------------|--------|---------|----------|--|
| Iron, Fe                      | 98 %   | 98 %    |          |  |

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China