

## Saint-Gobain CHR® H7525 Glass-Silicone Backing Silicone Adhesive Pressure Sensitive Tape

Category: Polymer, Adhesive, Tape, Thermoset, Silicone

## **Material Notes:**

Description: Silicone glass provides temperature resistance from  $-85 {\hat {\rm A}}^{\circ} {\rm F}$  to  $+500 {\hat {\rm A}}^{\circ} {\rm F}$  ( $-62 {\hat {\rm A}}^{\circ} {\rm C}$  to  $+260 {\hat {\rm A}}^{\circ} {\rm C}$ ) and exceptional tensile strength and abrasion resistance. Applications include thermal spray, grit blasting, electrical and thermal insulation gaskets, heat sealing, and diaphragms. This tape uses a silicone adhesive system. Perfect for extreme temperature applications, silicone adhesives perform in continuous operating temperatures from  $-100 {\hat {\rm A}}^{\circ} {\rm F}$  to  $500 {\hat {\rm A}}^{\circ}$  ( $-73 {\hat {\rm A}}^{\circ} {\rm C}$  to  $260 {\hat {\rm A}}^{\circ} {\rm C}$ ). Silicone-based adhesive systems exhibit good chemical resistance, retain electrical properties, and remove cleanly with little or no residue. All data based on a 0.0175 inch test sample. (Thickness given is for both backing and adhesive. Backing thickness is .015 inches.) Information provided by Saint Gobain Performance Products.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Saint-Gobain-CHR-H7525-Glass-Silicone-Backing-Silicone-Adhesive-Pressure-Sensitive-Tape.php

Mechanical Properties	Metric	English	Comments
Tear Strength	21.9 kN/m	125 pli	Initial Tear Strength

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	260 °C	500 °F	
Minimum Service Temperature, Air	-73.3 °C	-100 °F	

Descriptive Properties	Value	Comments
Color	White	

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China