

Saint-Gobain CHR® T903 TRIFOIL™ PTFE/Aluminum Foil Backing Silicone Adhesive Pressure Sensitive Tape

Category : Polymer , Adhesive , Tape

Material Notes:

Description: Aluminum and copper foil tapes offer high conformability, conductivity, and reflectivity at elevated temperatures. Aluminum is available with a fiberglass laminate for applications requiring higher tear strengths. Service temperatures range from -100°F to +500°F (-73°C to +260°C). Applications include thermal spray, aircraft repainting, EMI/RFI shielding, and electroplating. This tape uses a silicone adhesive system. Perfect for extreme temperature applications, silicone adhesives perform in continuous operating temperatures from -100°F to 500°F (-73°C to 260°C). Silicone-based adhesive systems exhibit good chemical resistance, retain electrical properties, and remove cleanly with little or no residue. All data based on a 0.005 inch test sample. (Thickness given is for both backing and adhesive. Backing thickness is .0035 inches.) Information provided by Saint Gobain Performance Products.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Saint-Gobain-CHR-T903-TRIFOIL-PTFEAluminum-Foil-Backing-Silicone-Adhesive-Pressure-Sensitive-Tape.php

Mechanical Properties	Metric	English	Comments
Elongation at Break	15 %	15 %	
Tear Strength	8.77 kN/m	50.0 pli	Initial Tear Strength

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	288 °C	550 °F	
Minimum Service Temperature, Air	-73.3 °C	-100 °F	

Descriptive Properties	Value	Comments
Color	Green	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China