

## Shandong Dongyue Polymer DF-21C PTFE Presintered Resin

Category : Polymer , Thermoplastic , Fluoropolymer , PTFE

### Material Notes:

Usage: The presintered resin is suitable for continuously extruding of all types, pushing and pressing PTFE rod, tube and special shape. Packing: PTFE is packed in double layer PVC bags inside and in hard circular barrels outside. Storage: PTFE should be stored in a clean, dry warehouse to protect from dust, moisture, etc. Transportation: The products are transported according to non-dangerous products. Heat, moisture, freezing and strong shock should be avoided during transportation. Over-bumpiness and compression is apt to make the resin bind together. Conformable with Q/DYG 007-2004 Information provided by Shandong Dongyue Polymer Material Co., Ltd

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Shandong-Dongyue-Polymer-DF-21C-PTFE-Presintered-Resin.php](http://www.lookpolymers.com/polymer_Shandong-Dongyue-Polymer-DF-21C-PTFE-Presintered-Resin.php)

Physical Properties	Metric	English	Comments
Bulk Density	0.500 - 0.800 g/cc	0.0181 - 0.0289 lb/in <sup>3</sup>	
Particle Size	>= 900 Åµm	>= 900 Åµm	

Thermal Properties	Metric	English	Comments
Melting Point	322 - 332 Å°C	612 - 630 Å°F	

Descriptive Properties	Value	Comments
Machining Method	Ram extrusion	
Powder Flow (g/min)	450	
Smoothness & Cleanliness	First Grade: Clean and white surface, no metal impurity, the impurity quantity from 1-3 mm doesn't exceed two  Qualified: Clean and white surface, no metal impurity, the impurity quantity from 1-3 mm doesn't exceed four	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China