

Shandong Guangyin GYBHVNP Polymer

Category : Polymer , Thermoplastic , Polyolefin

Material Notes:

Our GYBHVNP products are mainly applied in fuel pipes and brake pipes of automobile and hoses of air conditioner. Information provided by Shandong Guangyin

Order this product through the following link:

http://www.lookpolymers.com/polymer_Shandong-Guangyin-GYBHVNP-Polymer.php

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	≥ 50.0 MPa	≥ 7250 psi	ISO 3146
Elongation at Break	≥ 300 %	≥ 300 %	ISO 527
Flexural Strength	≥ 10.0 MPa	≥ 1450 psi	ISO 178
Izod Impact, Notched (ISO)	NB	NB	ISO 179/IeU
Izod Impact, Unnotched (ISO)	NB	NB	ISO 179/IeA

Thermal Properties	Metric	English	Comments
Melting Point	189 - 192 °C	372 - 378 °F	

Processing Properties	Metric	English	Comments
Moisture Content	≤ 0.20 %	≤ 0.20 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China