

Sibur 153-02K 1st Grade Polyethylene for Cable Production

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE , Low Density Polyethylene (LDPE), Wire/Cable Grade

Material Notes:

For application of insulation and protective coverings for wiring and cables by extrusion method.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Sibur-153-02K-1st-Grade-Polyethylene-for-Cable-Production.php

Physical Properties	Metric	English	Comments
Density	0.9185 - 0.922 g/cc	0.03318 - 0.0333 lb/in ³	
Melt Index of Compound	0.21 - 0.39 g/10 min	0.21 - 0.39 g/10 min	

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	>= 13.7 MPa	>= 1990 psi	
Elongation at Break	>= 600 %	>= 600 %	

Descriptive Properties	Value	Comments
Flow Limit at Tension	>9.8 MPa	
Number of Inclusions	<8 pcs	
Spread Flow Batch Error	<±12 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China