

Silberline Silvex[®] 420-15-C

Category : Other Engineering Material , Additive/Filler for Polymer

Material Notes:

Silvex[®] C grades are aluminum pigment flakes dampened with a plasticizer to help prevent the individual flakes from becoming airborne during handling and processing. They are well suited for use in liquid colorant applications where processing temperatures are below the volatilization point of the carrier. Silvex[®] C grades are compatible with a variety of resins including polyolefins and styrene. Silvex[®] C grades are dampened with a pharmaceutical grade mineral oil and are suitable for applications which require FDA compliance. Specific FDA compliance information is available upon request. In order to maintain optimum aesthetics, Silvex[®] grades should be dispersed properly. Applications: Plastics

Order this product through the following link:

http://www.lookpolymers.com/polymer_Silberline-Silvex-420-15-C.php

Physical Properties	Metric	English	Comments
Particle Size	345 μm	345 μm	

Thermal Properties	Metric	English	Comments
Flash Point	221 $^{\circ}\text{C}$	430 $^{\circ}\text{F}$	

Descriptive Properties	Value	Comments
% Carrier	15	
Carrier	Mineral Oil	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China