

SolVin Vinidur® 464SZ Polyvinyl Chloride grafted copolymer

Category : Polymer , Thermoplastic , Vinyl (PVC)

Material Notes:

TYPE Suspension graft copolymer of vinylchloride and an acrylate elastomer. Vinidur 464SZ has been developed for the extrusion of window profiles with high impact strength and good weathering properties. APPLICATIONS Extrusion : unplasticized PVC - profile - tubes/pipes - sheet, film - foam Information provided by SolVin.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SolVin-Vinidur-464SZ-Polyvinyl-Chloride-grafted-copolymer.php

Physical Properties	Metric	English	Comments
Volatile Organic Compounds (VOC) Content	<= 0.30 g/l	<= 0.30 g/l	ISO 1269
Apparent Bulk Density	0.610 g/cc	0.0220 lb/in ³	ISO 60
Particle Size	63 Åµm	63 Åµm	>90% greater than value; ISO 1624
	250 Åµm	250 Åµm	<2% greater than value; ISO 1624
Viscosity Test	102 cm ³ /g	102 cm ³ /g	Reduced viscosity, K value = 64; ISO 1628-2

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China