

Solvay RHODOLINE® 646 Surfactant

Category : Fluid

Material Notes:

Description: Highly effective mineral oil defoamer for latex processing. Identification: OIL BASE DEFOAMER Available in: North

America Applications: RHODOLINE® 646 may be post-added to a latex or coating color at a concentration of about 0.05 to 0.15%. For use in adhesives or paints, the suggested concentration is 2.5 to 5.0 pounds per 100 gallons of product. RHODOLINE® 646 may be stored over a wide range of temperatures. For ease of handling, storage above 40°F is recommended. If the product should solidify due to cold, warm to room temperature and mix well before use. Information provided by Rhodia, Rhodia has been acquired by Solvay.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-RHODOLINE-646-Surfactant.php

Physical Properties	Metric	English	Comments
Density	0.900 - 0.920 g/cc	0.0325 - 0.0332 lb/in³	RP-17617
pH	7.0 - 9.0	7.0 - 9.0	5% Solution; RP-0420
Viscosity	200 - 750 cP	200 - 750 cP	#2 SP @ 30 rpm; RP-0596
Ash	10 - 12 %	10 - 12 %	RP-0065

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Appearance	Opaque, Gray Liquid	RP-0064
Hegman Test	<6.0	Grind, RP-9186

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China