

Solvay RHODOLINE® LC-2 Surfactant

Category : Fluid

Material Notes:

Description: Highly efficient mineral oil based defoamers for flat to gloss paints, quick process foam knock down and high in-can persistency. Identification: DEFOAMER BLEND Available in: North America Applications: RHODOLINE® LC-2 is a general purpose, high hydrophobic silica type defoamer engineered for use in paints, adhesives, and inks. RHODOLINE® LC-2 is not dispersible in water and should be used as received. In paint formulations, the suggested starting point is 2 to 6 pounds of defoamer per 100 gallons of paint. For easy handling, RHODOLINE® LC-2 should be stored at temperatures above 50°F, but not above 100°F. Information provided by Rhodia, Rhodia has been acquired by Solvay.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-RHODOLINE-LC-2-Surfactant.php

Physical Properties	Metric	English	Comments
Density	0.830 - 0.870 g/cc	0.0300 - 0.0314 lb/in ³	RP-17617
Viscosity	600 - 1000 cP	600 - 1000 cP	#3 sp @ 60 rpm; RP-0596

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Appearance	Light Tan Opaque Liquid	RP-0064

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China