

Solvay Specialty Polymers Polymist® XPP 535 Polytetrafluoroethylene (PTFE)

Category: Polymer, Thermoplastic, Fluoropolymer, PTFE, PTFE Powder

Material Notes:

Polymist® XPP 535 a white PTFE micronized powder PTFE micronized powder composed of discrete particles. Designed for use in critical engineering and high end performance coatings and inks, Polymist® XPP 535 will improved non-stick properties and mar and abrasion resistance as well as slip and rub resistance. Uses: AdditiveAdditional Properties: Bulk Density - ASTM D4895 325 g/l; Grind in Oil - NPIRI 2.00; Melt Temperature - ASTM D3418 320 to 330 °C; Particle Size - Internal Method 10.0 Âμm; Particle Size - Internal Method 3.80 Âμm; Specific Surface Area - Internal Method 3.0 m²/gInformation provided by Solvay Specialty Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Specialty-Polymers-Polymist-XPP-535-Polytetrafluoroethylene-PTFE.php

Descriptive Properties	Value	Comments
Availability	Asia Pacific	
	Europe	
	North America	
Color	White	
Form	Powder	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China