

Solvay Specialty Polymers Polymist® XPP 538 Polytetrafluoroethylene (PTFE)

Category: Polymer, Thermoplastic, Fluoropolymer, PTFE, PTFE Powder

Material Notes:

Polymist® XPP 538 a white PTFE micronized powder PTFE micronized powder composed of discrete particles. Designed for use in critical engineering and high end performance coatings and inks, Polymist® XPP 538 will improved non-stick properties and mar and abrasion resistance as well as slip and rub resistance.Uses: AdditiveAdditional Properties: Bulk Density - ASTM D4895 400 g/l; Grind in Oil - NPIRI 2.50; Melt Temperature - ASTM D3418 320 to 330 °C; Particle Size - Internal Method 15.0 Âμm; Particle Size - Internal Method 4.50 Âμm; Specific Surface Area - Internal Method 3.0 m²/glnformation provided by Solvay Specialty Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Specialty-Polymers-Polymist-XPP-538-Polytetrafluoroethylene-PTFE.php

Descriptive Properties	Value	Comments
Availability	Asia Pacific	
	Europe	
	North America	
Color	White	
Form	Powder	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China