

Solvay Specialty Polymers Tecnoflon® FOR 421/U Fluoroelastomer

Category : Polymer , Thermoset , Fluoropolymer, TS , Thermoset Fluoroelastomer , Rubber or Thermoset Elastomer (TSE)

Material Notes:

TECNOFLON® FOR 421/U is a low viscosity cure incorporated fluoroelastomer copolymer. This grade is well suited for applications where superior flow, mold release, and excellent compression set are required. Tecnoflon® FOR 421/U can be compounded to meet the major fluoroelastomer specifications. Features: Copolymer; Fast Cure; Good Flow; Good Mold Release; Good Processability; Low Compression Set; Low Viscosity Uses: Belts/Belt Repair; Blending; Gaskets; Hose; Profiles; Seals; Sheet Additional Properties: Fluorine Content - 66 % Information provided by Solvay Specialty Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Specialty-Polymers-Tecnoflon-FOR-421U-Fluoroelastomer.php

Physical Properties	Metric	English	Comments
Mooney Viscosity	24 @Temperature 121 Â°C	24 @Temperature 250 Â°F	ML 1+10; ASTM D1646

Descriptive Properties	Value	Comments
Availability	Europe; North America	
Color	Off-White	
Form	Slab	
Processing Technique	Calendering; Compounding; Extrusion Injection Molding; Resin Transfer Molding	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China