

Solvay Specialty Polymers Tecnoflon® T 938 Fluoroelastomer

Category : Polymer , Thermoset , Fluoropolymer, TS , Thermoset Fluoroelastomer , Rubber or Thermoset Elastomer (TSE)

Material Notes:

TECNOFLON® T 938 is a medium viscosity fluoroelastomer terpolymer with 68.5% fluorine content. Tecnoflon® T 938 does not contain curatives: therefore the proper levels of Tecnoflon® FOR M1 and Tecnoflon® FOR M2 must be added to achieve the required properties. Tecnoflon® T 938 exhibits the chemical resistance typical of fluoroelastomer terpolymers. It is well suited for applications requiring better chemical resistance and/or long term heat resistance compared to fluoroelastomer copolymers. Features: Good Chemical Resistance; Good Heat Aging Resistance; Good Processability; High Heat Resistance; Medium Viscosity; Terpolymer Uses: Belts/Belt Repair; Blending; Gaskets; Hose; Profiles; Seals; Sheet; Valves/Valve Parts Additional Properties: Fluorine Content - 69 % Information provided by Solvay Specialty Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Specialty-Polymers-Tecnoflon-T-938-Fluoroelastomer.php

| Physical Properties | Metric | English | Comments |
|---------------------|----------------------------|----------------------------|---------------------|
| Mooney Viscosity | 66 @Temperature 121 Â°C | 66 @Temperature 250 Â°F | ML 1+10; ASTM D1646 |

| Descriptive Properties | Value | Comments |
|------------------------|---|----------|
| Availability | Europe; North America | |
| Color | Translucent | |
| Form | Slab | |
| Processing Technique | Calendering; Compounding | |
| | Compression Molding; Extrusion | |
| | Injection Molding; Resin Transfer Molding | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China