

Struktol TPW 604 Processing Additive

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer

Material Notes:

STRUKTOLÂ® TPW 604 is a blend of lubricants designed specifically for wood fiber/flour filled polyolefins. This product will provide improved surface quality, increased output rates and a wider processing window leading to overall improved processability. Applications: STRUKTOLÂ® TPW 604 can also be used in other polyolefin compounds where improved processability or output rates are required. Information provided by Struktol

Order this product through the following link:

http://www.lookpolymers.com/polymer_Struktol-TPW-604-Processing-Additive.php

Physical Properties	Metric	English	Comments
Additive Loading	2.0 - 7.0 %	2.0 - 7.0 %	

Thermal Properties	Metric	English	Comments
Dropping Point	95.0 - 113 Â°C	203 - 235 Â°F	

Processing Properties	Metric	English	Comments
Shelf Life	>= 24.0 Month	>= 24.0 Month	

Descriptive Properties	Value	Comments
Appearance	Off-white to light tan pastille or bead	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China