Synergy Polymers Ultra Purge P-O

Category : Polymer , Thermoplastic , Purging Compound

Material Notes:

Ultra Purge is a specially designed cleaning compound that comes premixed and ready-to-use in pellet form. It cleans black specks and deposits from screws, barrels, nozzle, hot runners and heads of extruders when doing periodic cleaning or when changing color for all thermoplastics. Purged Resin: Works with all thermoplastics including: HDPE, LDPE, PP, (PS), Polyolefinic resin. Information provided by Synergy Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Synergy-Polymers-Ultra-Purge-P-0.php

Physical Properties	Metric	English	Comments
Density	0.700 g/cc	0.0253 lb/in³	

Thermal Properties	Metric	English	Comments
Melting Point	70.0 °C	158 °F	
Maximum Service Temperature, Air	300 °C	572 °F	
Minimum Service Temperature, Air	170 °C	338 °F	
Decomposition Temperature	>= 85.0 °C	>= 185 °F	Avoid temperature > 80°C except during use
Flammability Test	>= 300	>= 300	[°C] In flammability point
	>= 450	>= 450	[°C] Ignition temperature

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China