

TIMCAL TIMREX® FC250 Coke

Category : Carbon , Other Engineering Material , Additive/Filler for Polymer

Material Notes:

TIMREX Petroleum Coke is calcined at appropriate temperature with low ash and sulfur (sulphur) content, well defined texture and consistent particle size distribution. Advantages and applications: Suitable for all kind of sintered and organic bonded friction materials. Low wear of counterpart due to low ash content Stable friction coefficient, non-fading High thermal stability Reduction of noise, especially medium and high frequency sounds Information provided by TIMCAL

Order this product through the following link:

http://www.lookpolymers.com/polymer_TIMCAL-TIMREX-FC250-Coke.php

Physical Properties	Metric	English	Comments
Bulk Density	0.910 g/cc	0.0329 lb/in ³	Tap
Particle Size	250 µm	250 µm	
Deformation	0.10 %	0.10 %	elastic
	0.21 %	0.21 %	plastic
	6.4 %	6.4 %	plastic + elastic
Ash	0.070 %	0.070 %	

Mechanical Properties	Metric	English	Comments
Coefficient of Friction	0.51 @Temperature 850 °C, Time 10800 sec	0.51 @Temperature 1560 °F, Time 3.00 hour	Friction coefficient of sintered Cu-C - brake pads with 10% TIMREX® Coke, Sinter density: 53% of the theoret. density

Thermal Properties	Metric	English	Comments
Thermal Conductivity	12.0 W/m-K	83.3 BTU-in/hr-ft ² -°F	

Processing Properties	Metric	English	Comments
Moisture Content	0.020 %	0.020 %	

Descriptive Properties	Value	Comments
Crystallite height Lc	2.5	
DBP absorption	6 g/100g	(Dibutylphthalate)

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China